





		UNLESS OTHERWISE SPECIFIED:	
	REVISION NOTES AND DATES	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS:  1 PLACE DECIMAL (.0): ±.030	
		2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°	
		SURFACE FINISH: 63RMS	
PROPRIETARY AND CONFIDENTIAL		BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS		THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY	

	NAME	DATE	
DRAWN	MH	06/30/2020	
CHECKED	KH	06/30/2020	
DATE STARTED IN PRODUCTION:		ODUCTION:	
06/30/2020			
	CHECKED	DRAWN MH CHECKED KH DATE STARTED IN PRO	DRAWN MH 06/30/2020 CHECKED KH 06/30/2020 DATE STARTED IN PRODUCTION:

<b>ULTRA PRESSURE COMPONENTS</b>
HOUSTON, TX

TITLE:

9/16" High Pressure Plug 60,000 psi

SIZE DWG. NO. 5406P-9H REV

SCALE: 2:1

WEIGHT: 0.16

SHEET 1 OF 1

PROHIBITED.