


1" Type M Male  
1"-12UNF Thread

1" MP Male  
1-3/8"-12UNF Thread



SECTION A-A

REVISION NOTES AND DATES

UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES  
TOLERANCES AS FOLLOWS:  
1 PLACE DECIMAL (.0): ±.030  
2 PLACE DECIMAL (.00): ±.020  
3 PLACE DECIMAL (.000): ±.010  
ANGLES: ±2°

SURFACE FINISH: 63RMS  
BREAK ALL EDGES: .010-.015  
FILLETS & ROUNDINGS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B  
CHAMFER THREADS 45° TO ROOT  
30° CHAMFER IS OPTIONAL  
FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	BM	8/18/2020
CHECKED	KH	8/18/2020
DATE STARTED IN PRODUCTION:		
8/18/2020		



We can handle Pressure

**ULTRA PRESSURE COMPONENTS  
HOUSTON, TX**

TITLE:

1" MP Male x 1" Type M Male  
20,000 psi

SIZE	DWG. NO.	REV
<b>A</b>	5404-16MM16-CUST	<b>1</b>

SCALE: 1:1	WEIGHT: 0.86	SHEET 1 OF 1
------------	--------------	--------------

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.