

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS


DRAWING IS THE SOLE PROPERTY OF


ULTRA PRESSURE COMPONENTS. ANY

PROHIBITED.

REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS

5





1"-11.5NPT 9/16" Medium Pressure Male Male Connection (13/16"-16UNF Thread)

revision notes and dates	TOLERANCES AS FOLLOWS:
	1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°
	SURFACE FINISH: 63RMS BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30
	THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL

	UNLESS OTHERWISE SPECIFIED:		NAME	DATE
	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS:	DRAWN	ВМ	9/13/2022
1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010	CHECKED	KH	09/28/2022	
	DATE STARTED IN PRODUCTION:			
ANGLES: ±2°		09/28/2022		
	SURFACE FINISH: 63RMS BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30			

ULTRA PRESSURE COMPONENTS HOUSTON, TX

22 TITLE:

1" NPT Male x 9/16" MP Male 10,000 psi



SIZE DWG. NO. 5404-16N9M **REV**

SCALE: 1:1

WEIGHT: 0.69

SHEET 1 OF 1

FOR MALE THREADS ONLY