


**REVISION NOTES AND DATES** 



1-1/2"-11.5NPT 1-5/16" Type M Male Male Thread 1-5/16"-12UN Thread

## UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS: 1 PLACE DECIMAL (.0): ±.020 2 PLACE DECIMAL (.00): ±.010 3 PLACE DECIMAL (.000): ±.005 ANGLES: ±2°

SURFACE FINISH: 63RMS BREAK ALL EDGES: .010-.015 FILLETS & ROUINDS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY

## **ULTRA PRESSURE COMPONENTS** NAME DATE HOUSTON, TX 7/19/23 BM7/19/23

TITLE:

**SECTION A-A** 

1-1/2" MALE NPT X 1-5/16" TYPE M 7,500 PSI



KΗ

DATE STARTED IN PRODUCTION:

7/19/23

DRAWN

CHECKED

SIZE DWG. NO.

5404-24NM21

**REV** 

SCALE: 1:1

WEIGHT: 1.63

SHEET 1 OF 1

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.

> 5 3 2