





1/4"-18NPT Male Connection **Both Ends**

SECTION A-A

		LINILEGE OTHERWISE CRECIEIED.
		UNLESS OTHERWISE SPECIFIED:
		ALL DIMENSIONS ARE IN INCHES
	DEVICIONI NIOTEC ANID DATEC	TOLERANCES AS FOLLOWS:
	revision notes and dates	1 PLACE DECIMAL (.0): ±.030
		2 PLACE DECIMAL (.00): ±.020
		3 PLACE DECIMAL (.000): ±.010
		ANGLES: ±2°
		SURFACE FINISH: 63RMS
		BREAK ALL EDGES: .010015
PROPRIETARY AND CONFIDENTIAL		FILLETS & ROUINDS: R.015 - 0.30
THE INFORMATION CONTAINED IN THIS		
DRAWING IS THE SOLE PROPERTY OF		THREADS UNIFIED CLASS 2A - 2B
ULTRA PRESSURE COMPONENTS. ANY		CHAMFER THREADS 45° TO ROOT

IFIED:		NAME	DATE	
HES 30 020 :.010	DRAWN	MH	05/24/2022	
	CHECKED	KH	05/24/2022	1
	DATE STARTED IN PRODUCTION:			
	05/24/2022			



ULTRA PRESSURE COMPONENTS HOUSTON, TX

TITLE:

1/4" x 6" NPT Male Hex Nipple 15,000 psi

SIZE DWG. NO.

5404-4N4N_6.0

REV

SCALE: 1:1.5 WEIGHT: 0.49 SHEET 1 OF 1

5

REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF

ULTRA PRESSURE COMPONENTS IS

PROHIBITED.

30° CHAMFER IS OPTIONAL

FOR MALE THREADS ONLY

2