







	UNLESS OTHERWISE SPECIFIED
REVISION NOTES AND DATES	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS: 1 PLACE DECIMAL (.0): ±.030
	2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°
	SURFACE FINISH: 63RMS BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30

FIED: NAME DATE **ULTR**ES DRAWN MH 08/04/2022

CHECKED KH 08/04/2022

DATE STARTED IN PRODUCTION:

08/04/2022

3/8" NPT Male x 1" MP Male 15,000 psi

WEIGHT: 0.79

ULTRA PRESSURE COMPONENTS

HOUSTON, TX

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF

5

ULTRA PRESSURE COMPONENTS IS

PROHIBITED.

PROPRIETARY AND CONFIDENTIAL

THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY

ultra Pressure
Components
We can handle Pressure

SIZE DWG. NO. 5404-6N16M

SCALE: 1:1

REV Y SHEET 1 OF 1

4 3