





5

1/2"-14NPT 1/4" High Pressure Male Male Thread 9/16"-18UN Thread

		OTTLESS OTTLER TISE STECTILES.
	REVISION NOTES AND DATES	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS:
		1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		SURFACE FINISH: 63RMS BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30
ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.		THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY

	UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ULTI	RA PRESSURE COMPON	ENTS
	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS:	DRAWN	ВМ	11/7/2022	HOUSTON, TX		
	1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020	CHECKED	KH	12/01/2022	TITLE:		
		DATE STARTED IN PRODUCTION:		,	/O!! NIDT A A LE V 1 / 4!! ID		
3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°		12/01/2022		1/2" NPT MALE X 1/4"HP MALE 15,000 MAWP			
	SURFACE FINISH: 63RMS	0			13,000 MAVVF		
	BREAK ALL EDGES: .010015	(Vulue)					
	FILLETS & ROUINDS: R.015 - 0.30			SIZE	DWG. NO.	REV	
	THREADS UNIFIED CLASS 2A - 2B	tra	ultra Pressure		Λ	5404-8N4H	V
	CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL	uldia.	TIGE D			J404-0114H	

SCALE: 1:1

WEIGHT: 0.21

SHEET 1 OF 1

3 2