|  |                               |   |   |      | 2.0     |  |  |
|--|-------------------------------|---|---|------|---------|--|--|
|  | A Male Thread<br>(Both Sides) |   |   |      |         |  |  |
| A  |                               |   | SECTION A-A                             |      |         |  |  |
|  |                               |   |   |      |         |  |  |
|  |                               | UNLESS OTHERWISE SPECIFIED:   | :                                       | NAME | DATE    | ULTRA PRESSURE COMPONENTS  |  |
|  | REVISION NOTES AND DATES      | ALL DIMENSIONS ARE IN INCHES<br>TOLERANCES AS FOLLOWS:  | DRAWN                                   | BM   | 6/19/23 | HOUSTON, TX  |  |
| -  | REVISION NOTES AND DATES      | 1 PLACE DECIMAL (.0): ±.020<br>2 PLACE DECIMAL (.00): ±.010   | CHECKED                                 | KH   | 6/19/23 | TITLE:   |  |
|  |                               | 3 PLACE DECIMAL (.000): ±.005<br>ANGLES: ±2°  | DATE STARTED IN PRODUCTION:             |      |         | 1/2" NPT Male x 2.00" Round  |  |
|  |                               | SURFACE FINISH: 63RMS   | 06/23/2023                              |      |         | MAWP 15,000 PSI  |  |
| PROPRIETARY AND CONFIDENTIAL<br>THE INFORMATION CONTAINED IN THIS<br>DRAWING IS THE SOLE PROPERTY OF<br>ULTRA PRESSURE COMPONENTS. ANY<br>REPRODUCTION IN PART OR AS A WHOLE<br>WITHOUT THE WRITTEN PERMISSION OF<br>ULTRA PRESSURE COMPONENTS IS<br>PROHIBITED. |                               | BREAK ALL EDGES: .010015<br>FILLETS & ROUINDS: R.015 - 0.30<br>THREADS UNIFIED CLASS 2A - 28<br>CHAMFER THREADS 45° TO ROOT<br>30° CHAMFER IS OPTIONAL<br>FOR MALE THREADS ONLY | Utra Pressure<br>we can handle Pressure |      | GIB     | SIZE DWG. NO. REV   A 5404N-8N2.0 Y   SCALE: 1.5:1 WEIGHT: 0.22 SHEET 1 OF 1 |  |
| 5  | ₫ 4                           | 3   |   |      | 2       | 1  |  |