





1/2"-14 NPT Male (Both Sides) per MASTER\_8NM **SECTION A-A** 

		UNLESS OTHERWISE SPECIFIE
	REVISION NOTES AND DATES	1) DIMENSIONS ARE IN INCHES 2) TOLERANCES: FRACTIONAL± 1/64"
		ANGULAR: MACH± 2°  ONE PLACE DECIMAL ± .020  TWO PLACE DECIMAL ± .010  THREE PLACE DECIMAL ± .000  3) THREADS UNIFIED CLASS
PROPRIETARY AND CONFIDENTIAL		2A - 2B
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY		4) SURFACE FINISH 63uin Ra 5) CHAMFER THREADS: MALE - 30 ° TO ROOT
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF		FEMALE - 45 ° TO ROOT

UNLESS OTHERWISE SPECIFIED:
1) DIMENSIONS ARE IN INCHES 2) TOLERANCES: FRACTIONAL± 1/64" ANGULAR: MACH± 2° ONE PLACE DECIMAL ± .020 TWO PLACE DECIMAL ± .010
THREE PLACE DECIMAL ± .005 3) THREADS UNIFIED CLASS 2A - 2B 4) SURFACE FINISH 63uin Ra 5) CHAMFER THREADS: MALE - 30 ° TO ROOT FEMALE - 45 ° TO ROOT

	NAME	DATE	
DRAWN	MH	9/6/2017	
CHECKED	KH	9/6/2017	1
DATE STARTED IN PRODUCTION:			
9/6/2017			



<b>ULTRA PRESSURE COMPONENTS</b>
HOUSTON, TX

TITLE:

1/2" NPT Male x 4.00" Nipple 15,000 psi

SIZE DWG. NO. 5404N-8N4.0

SCALE: 1:1

WEIGHT: 0.50

SHEET 1 OF 1

REV

5

ULTRA PRESSURE COMPONENTS IS

PROHIBITED.

2