


1/4" HP Male
9/16"-18UN Thread



SECTION A-A

REVISION NOTES AND DATES

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN INCHES
TOLERANCES AS FOLLOWS:
1 PLACE DECIMAL (.0): $\pm .030$
2 PLACE DECIMAL (.00): $\pm .020$
3 PLACE DECIMAL (.000): $\pm .010$
ANGLES: $\pm 2^\circ$

SURFACE FINISH: 63RMS
BREAK ALL EDGES: .010-.015
FILLETS & ROUNDS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B
CHAMFER THREADS 45° TO ROOT
30° CHAMFER IS OPTIONAL
FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	BM	9/11/2020
CHECKED	KH	9/11/2020
DATE STARTED IN PRODUCTION:		
9/11/2020		



ULTRA PRESSURE COMPONENTS HOUSTON, TX

TITLE:
1/4" HP Male x 1/4" NPT Female
15,000 psi

SIZE A	DWG. NO. 5406-4N4H	REV 1
SCALE: 2:1	WEIGHT: 0.14	SHEET 1 OF 1