


7/8" Type M Male 7/8"-14UN Thread per MASTER\_M14 (BOTH SIDES)



	UNLESS OTHERWISE SPECIFIED:
REVISION NOTES AND DATES	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS:
REVISION NOTES AND DATES	1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010
	ANGLES: ±2°  SURFACE FINISH: 63RMS

BREAK ALL EDGES: .010-.015 FILLETS & ROUINDS: R.015 - 0.30

THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	MH	07/16/2020
CHECKED	KH	07/16/2020

DATE STARTED IN PRODUCTION:

07/16/2020

## We can handle Pressure

## **ULTRA PRESSURE COMPONENTS** HOUSTON, TX

TITLE:

7/8" Type M Male x 7/8" Type M Male 40,000 psi

SIZE DWG. NO.

**REV** 

5404-M14M14

SHEET 1 OF 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE

PROPRIETARY AND CONFIDENTIAL

WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS

5

PROHIBITED.

3

2

SCALE: 1.5:1 WEIGHT: 0.33