





		UNLESS OTHERWISE SPECIFIED:
	REVISION NOTES AND DATES	TOLERANCES AS FOLLOWS: 1 PLACE DECIMAL (.0): ±.030
		2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2°
PROPRIETARY AND CONFIDENTIAL		SURFACE FINISH: 63RMS BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF		THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY

):		NAME	DATE	
	DRAWN	ВМ	07/30/2020	
	CHECKED	KH	07/30/2020	-
	DATE STARTED IN PRODUCTION:			

07/30/2020

ultra Pressure components We can handle Pressure

ULTRA PRESSURE COMPONENTS HOUSTON, TX

TITLE:

1/2" Female NPT 2-Way Angle Needle Valve - 15,000 psi

Δ Δ

SIZE DWG. NO.

REV

NV2A8N-15K

SCALE: 1:2 WEIGHT:

EIGHT: SHEET 1 OF 1

5

ULTRA PRESSURE COMPONENTS IS

PROHIBITED.

1

3

2

I

1